

# EZ PULL COLD

## COLD WEATHER WIRE PULLING LUBRICANT

**PRODUCT NAME** EZ Pull - Wire Pulling Lubricant

**MANUFACTURER** Everkem Diversified Products  
 120 Regent Drive, Winston Salem, NC 27103  
 PH: 1-800-638-3160 | FAX: (336) 661-7969

**PRODUCT DESCRIPTION** EZ-Pull is a premium grade lubricating gel specially formulated for cold weather wire pulling applications in temperatures as low as -20°F (-28.9°C). EZ Pull Cold reduces friction, making difficult wire pulls quick and easy - even in cold weather. EZ Pull is compatible with all cable jackets, is non-corrosive, and non-toxic.

- APPLICATIONS**
- Pulling light weight communication and data network cables including fiber optic cables
  - Pulling industrial power and telecom cables over long distances
  - For long cable pulls and difficult cable pulling applications

- ADVANTAGES**
- Meets IEEE standards
  - Meets ASTM-D1693 performance criteria
  - Performance in temperatures as low as -20°F (-28.9°C).
  - Safe for all commonly used materials such as rubber, neoprene, nylon, PVC, PE, and more.
  - Will not clog or corrode conduit
  - Exceptional lubricity & cling characteristics
  - Dried lubricant on cables can be re-wet.
  - For indoor or outdoor use
  - Non-staining, easy cleanup

**LIMITATIONS** EZ Pull Cold is not for use as a protective barrier for cables, cable jackets. EZ Pull is not for use as a conductivity improvement substance.

**AVAILABLE COLORS** EZ Pull Cold is available in Translucent Red

**TECHNICAL DATA**

**TYPICAL PHYSICAL PROPERTIES**

Chemistry:	Water-based
Appearance:	Translucent red gel
Application Temperature:	-30°F to 120°F (-34.4°C to 48.9°C)
Service Temperature:	Stable over -20°F to 120°F (-28.9°C to 82.2°C) range
pH level:	7 - 8
Shelf Life:	2 years
Dried State:	Dries to a clear film
Freeze - Thaw:	Excellent
ASTM-D1693:	Meets ASTM-D1693 "Standard Test Method for Environmental Stress Cracking of Ethylene Plastics"
V.O.C. Content:	8.5 g/L

# EZ PULL COLD

## COLD WEATHER WIRE PULLING LUBRICANT

APPLICABLE STANDARDS & SPECIFICATIONS

**SPECIFIED DIVISIONS**

- Section 26 00 00 - Electrical
- Section 27 00 00 - Communications

**APPLICABLE STANDARDS/SPECIFICATIONS**

- ASTM-D1693- Standard Test Method for Environmental Stress-Cracking of Ethylene Plastics

**ECOSEAL STANDARDS**

- V.O.C. Content: 8.5 g/L

**INSTALLATION**

SURFACE PREPARATION

Ensure the item to be pulled is in safely operable condition prior to pulling.

APPLICATION

1. Apply liberal amounts of EZ Pull lubricant directly to cables, wires, etc by hand, brush, or pump as they are being fed into the conduit.
2. Be sure to clean excess lubricant from wires and allow sufficient drying time before energizing the circuit.

CLEANUP

The product is extremely slippery. To avoid slips, trips, and falls promptly clean up any spillage of product. Excess product should be cleaned off tools and nonporous surfaces when application is complete using water and a dry cloth or paper towels. Excessive amounts may require the use of a solvent such as acetone or mineral spirits.

**AVAILABILITY**

EZ Pull and other Everkem products are available from stocking distributors nationwide or direct from the manufacturer. For the name and telephone number of the nearest Everkem representative, call the number below or visit [www.everkemproducts.com](http://www.everkemproducts.com)

PACKAGING OPTIONS

PACKAGING OPTIONS			
Part #	Description	Packaging	Color
EZ-PullWG-32	EZ Pull - 32 Fl. Oz. (946.4mL) Bottle	12 bottles/case	Translucent Red
EZ-PullWG-1	EZ Pull - 1 Gallon (3.79L) Pail	4 pails/case	Translucent Red
EZ-PullWG-5	EZ Pull - 5 Gallon (18.9L) Pail	Each	Translucent Red
EZ-PullWG-55	EZ Pull - 55 Gallon (208.2L) Drum	Each	Translucent Red

**MAINTENANCE**

Follow the cable, conduit, etc manufacturer's maintenance schedule. If new cables, wires, etc are required, use EZ Pull Cold for these pulling applications.

**TECHNICAL SERVICES**

Everkem representatives are available to assist you in selecting the sealant or adhesive appropriate for your application. For further assistance contact your local Everkem Diversified Products representative, call our corporate office at 1-800-638-3160, or contact us via our website at [www.everkemproducts.com](http://www.everkemproducts.com)

# EZ PULL COLD

## COLD WEATHER WIRE PULLING LUBRICANT

### WARRANTY

Everkem Diversified Products warrants this product's performance provided it is properly stored and applied within 2 years. If when applied as directed this material proves to be defective, return the remaining product and proof of purchase for refund or replacement of product exclusive of labor or cost of labor. This is the sole and exclusive remedy for defects of product failure. The determination of eligibility for this warranty shall be made at the sole discretion of Everkem Diversified Products and any decision made shall be final. This warranty is in lieu of any other warranties, expressed or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose, and in no instance will Everkem Diversified Products be liable for damages in excess of the purchase price, except where such exclusion or limitation is prohibited by state law. Users must read and follow the directions of the current Technical Data Guide and SDS prior to product use. The user determines the suitability of the product intended for use and assumes all risks. Recommendations for the use of this product are based on tests we believe to be reliable. The manufacturer and seller are not responsible for results where the product is used under conditions not in strict accordance with our published recommendations and in applications considered suitable for this product. Everkem Diversified Products shall not be responsible for the use of this product in a manner to infringe upon any patent or any other intellectual property rights held by others.

### CAUTIONS



**WARNING: MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL TO AQUATIC LIFE WITH LONG-LASTING EFFECTS.** Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling. **IF ON SKIN:** Wash with soap and water. Remove contaminated clothing, washing before reuse. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water. Remove contact lenses if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention. **IF INGESTED:** Wash mouth with water. Remove victim to fresh air. Give small quantities of water to drink. Do not induce vomiting. Store locked up. Dispose of contents in accordance with all local, regional, national, and international regulations. **KEEP OUT OF REACH FROM CHILDREN.**



**WARNING:** This product can expose you to 2,2'-Iminodiethanol, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Everkem Diversified Products  
 120 Regent Drive | Winston-Salem, NC | 27103  
 1-800-638-3160 | [www.everkemproducts.com](http://www.everkemproducts.com)

Last Revised: 5/2021