

THE EVERKEM EXPERIENCE

Our values, our people, and our products are all part of a much larger commitment to you, something we like to call the Everkem Experience.

The Everkem Experience isn't tangible. It's a state of mind, a way of building partnerships. It's a dedication to doing the small things that others don't, with the deep belief that these little things make the biggest impacts.



QUALITY PRODUCTS



LOW FREIGHT MINIMUM



EXCEPTIONAL SERVICE



◀  SCAN TO VIEW DIGITAL CATALOG



120 REGENT DRIVE,
WINSTON-SALEM, NC 27103

FIRESTOPPING | PERFORMANCE SEALANTS | HIGH STRENGTH ADHESIVES | FOAM SEALANTS | ELECTRICAL CHEMICALS
www.everkemproducts.com | 1-800-638-3160



HVAC
PRODUCT LINE



TRUSIL 100

NSF CERTIFIED 100% SILICONE SEALANT

SPECIFICATIONS

- 100% Silicone
- NSF 51 Certified
- Meets ASTM-C920
- Meets federal specs TT-S-00230C, TT-S-01543A
- Meets FDA Reg No. 21 CFR 177

FEATURES

- +/-25% joint movement
- 50+ Year durability
- High temp performance (up to 400°F)
- Low temperature flexibility (to -55°F)
- Mildew resistant
- Non-sagging
- Low V.O.C.'s
- Available in clear, white, black, & aluminum



Also available in 2.8 oz. squeeze tubes in white and clear



TRUSIL HTS

HI-TEMP SILICONE SEALANT

SPECIFICATIONS

- NSF 51 Certified
- Meets ASTM-C920
- Meets federal specs TT-S-00230C, TT-S-01543A
- Meets FDA Reg No. 21 CFR 177

FEATURES

- High temperature performance
- +/-25% joint movement
- 50+ Year durability
- Exposure up to 600°F
- Low temperature flexibility
- Mildew resistant
- Low V.O.C.'s



FULL-FILL GP

GENERAL PURPOSE GAPS & CRACKS



FEATURES

- Economically insulates, fills, seals
- For use in interior and exterior applications
- Prevents cold air infiltration and heat loss
- Improves energy efficiency
- Adheres to a wide array of common construction materials
- High yield formulation
- Tack free in as little as 10 minutes
- Easy to use

FLAMETECH FB

FIREBLOCKING FOAM



FEATURES

- UL recognized alternative fireblocking material
- For use in Type V residential construction
- Easy to use
- 1 can yields up to 15 tubes of caulk
- Reduces labor costs
- Improves energy efficiency
- Identifiable orange color

FIRE SEAL-136

RESIDENTIAL FIREBLOCKING CAULK



SPECIFICATIONS

- Tested to ASTM-E814 (UL 1479)
- Tested to ASTM-E136
- UL classified

FEATURES

- Great adhesion
- Smooth consistency
- For single family, non-rated penetrations
- Red color
- Low V.O.C.'s

FIRESTOP-814+

INTUMESCENT FIRESTOPPING CAULK

SPECIFICATIONS

- Tested to ASTM-E814 (UL 1479)
- Tested to ASTM-E1966 (UL 2079)
- Meets LEED v4 Emissions requirements (CDPH SM / CA Section 01350)

FEATURES

- Up to a 4 Hour fire rating
- For use in multi-family & commercial construction
- Red color
- CPVC compatible
- Excellent freeze/thaw
- Smooth consistency
- Intumescent
- Elastomeric
- Low V.O.C.'s



Available in 10.1 oz. tubes, 20 oz. sausage tubes, 28 oz. tubes, & 5 gallon pails

FIRE PATCH

FURNACE & RETORT CEMENT

SPECIFICATIONS

- Meets ASTM-C199
- Meets ASTM-E136
- PCE Value 17-18
- Tested to ASTM-C24 Pyrometric Cone Equivalency Test - 2700°F

FEATURES

- Pre-mixed
- Smooth consistency
- Low V.O.C.'s
- Easy cleanup



Available in 1/2 gallon or 1 gallon pails