

EZ PULL WAX

WAX WIRE PULLING LUBRICANT

PRODUCT NAME EZ Pull Wax - Wax-Based Wire Pulling Lubricant

MANUFACTURER Everkem Diversified Products
 120 Regent Drive, Winston Salem, NC 27103
 PH: 1-800-638-3160 | FAX: (336) 661-7969

PRODUCT DESCRIPTION EZ-Pull Wax is a premium wax-based lubricant that reduces friction and limits surface tension, making difficult wire pulling applications quick and easy. EZ Pull Wax is compatible with all cable jackets, UL Listed, and tested to ASTM-D1693 for Environment Stress Cracking Standards. EZ Pull Wax has excellent cling characteristics, is non-corrosive, and non-toxic.

- APPLICATIONS**
- Ideal for heavy-duty cable pulls, including industrial power and telecom cables
 - Designed for long-distance and high-tension pulling applications
 - Thick, high-cling wax formula stays on cable through extended pulls
 - Exceptional lubricity lowers pulling tension, helping prevent cable damage and costly rework

- ADVANTAGES**
- Meets IEEE standards
 - Tested to ASTM-D1693 performance criteria
 - UL Listed (UL 276)
 - Safe for all cable types including LDPE, neoprene, nylon, PVC, semi-conducting jackets
 - Non-corrosive formula won't clog or damage conduit over time

LIMITATIONS EZ Pull Wax is not for use as a protective barrier for cables, cable jackets. EZ Pull is not for use as a conductivity improvement substance.

AVAILABLE COLORS EZ Pull Wax is available in Yellow

TECHNICAL DATA

TYPICAL PHYSICAL PROPERTIES	
Typical Uncured Properties	
Chemistry:	Wax-based
Appearance:	Yellow wax
Service Temperature:	Stable over 30°F to 130°F (-1.1°C to 54°C) range
Application Temperature:	32°F to 120°F (0°C to 48.9°C)
pH Level:	7 - 8
Freeze - Thaw:	Excellent
ASTM-D1693:	Meets ASTM-D1693 "Standard Test Method for Environmental Stress-Cracking of Ethylene Plastics"
V.O.C. Content:	<10%
Shelf - Life:	2 years

EZ PULL WAX

WAX WIRE PULLING LUBRICANT

APPLICABLE STANDARDS & SPECIFICATIONS

SPECIFIED DIVISIONS

- Section 26 00 00 - Electrical
- Section 27 00 00 - Communications

APPLICABLE STANDARDS/SPECIFICATIONS

- ASTM-D1693- Standard Test Method for Environmental Stress-Cracking of Ethylene Plastics

ECOSEAL STANDARDS

- V.O.C. Content: <10%

INSTALLATION

SURFACE PREPARATION

Ensure item to be pulled is in safely operable condition prior to pulling.

APPLICATION

1. Apply liberal amounts of EZ Pull Wax lubricant directly to cables, wires, etc by hand, brush, or pump as they are being fed into the conduit.
2. Be sure to clean excess lubricant from wires and allow sufficient drying time before energizing the circuit.

CLEANUP

The product is extremely slippery. To avoid slips, trips, and falls promptly clean up any spillage of product. Excess product should be cleaned off tools and nonporous surfaces when the application is complete using water and a dry cloth or paper towels. Excessive amounts may require the use of a solvent such as acetone or mineral spirits.

AVAILABILITY

EZ Pull Wax and other Everkem products are available from stocking distributors nationwide or direct from the manufacturer. For the name and telephone number of the nearest Everkem representative, call the number below or visit www.everkemproducts.com

PACKAGING OPTIONS

PACKAGING OPTIONS			
Part #	Description	Packaging	Color
EZ-Pull-32YW	EZ Pull Wax - 32 Fl. Oz. (946.4mL) Bottle	12 bottles/case	Yellow
EZ-Pull-1YW	EZ Pull Wax - 1 Gallon (3.79L) Pail	4 pails/case	Yellow
EZ-Pull-5YW	EZ Pull Wax - 5 Gallon (18.9L) Pail	Each	Yellow
EZ-Pull-55YW	EZ Pull Wax - 55 Gallon (208.2L) Drum	Each	Yellow

MAINTENANCE

Follow the cable, conduit, etc manufacturer's maintenance schedule. If new cables, wires, etc are required, use EZ Pull Wax for these pulling applications.

TECHNICAL SERVICES

Everkem representatives are available to assist you in selecting the sealant or adhesive appropriate for your application. For further assistance contact your local Everkem Diversified Products representative, call our corporate office at 1-800-638-3160, or contact us via our website at www.everkemproducts.com

EZ PULL WAX

WAX WIRE PULLING LUBRICANT

WARRANTY

Everkem Diversified Products warrants this product's performance provided it is properly stored and applied within 2 years. If when applied as directed this material proves to be defective, return the remaining product and proof of purchase for refund or replacement of product exclusive of labor or cost of labor. This is the sole and exclusive remedy for defects of product failure. The determination of eligibility for this warranty shall be made at the sole discretion of Everkem Diversified Products and any decision made shall be final. This warranty is in lieu of any other warranties, expressed or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose, and in no instance will Everkem Diversified Products be liable for damages in excess of the purchase price, except where such exclusion or limitation is prohibited by state law. Users must read and follow the directions of the current Technical Data Guide and SDS prior to product use. The user determines the suitability of the product intended for use and assumes all risks. Recommendations for the use of this product are based on tests we believe to be reliable. The manufacturer and seller are not responsible for results where the product is used under conditions not in strict accordance with our published recommendations and in applications considered suitable for this product. Everkem Diversified Products shall not be responsible for the use of this product in a manner to infringe upon any patent or any other intellectual property rights held by others.

CAUTIONS



WARNING: MAY CAUSE ALLERGIC SKIN REACTION. HARMFUL TO AQUATIC LIFE WITH LONG LASTING EFFECTS. Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling. **IF ON SKIN:** Wash with soap and water. Remove contaminated clothing, washing before reuse. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water. Remove contact lenses if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention. **IF INGESTED:** Wash mouth with water. Remove victim to fresh air. Give small quantities of water to drink. Do not induce vomiting. Store locked up. Dispose of contents in accordance with all local, regional, national, and international regulations. **KEEP OUT OF REACH FROM CHILDREN.**



WARNING: This product can expose you to chemicals including Coconut diethanolamide and Diethanolamine, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



Everkem Diversified Products
 120 Regent Drive | Winston-Salem, NC | 27103
 1-800-638-3160 | www.everkemproducts.com

Last Revised: 3/2026