



Safety Data Sheet Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Section 1. Identification

Product identifier

Product Identity

Roof Goo, All Weather Flashing Cement

Other means of identification

Not Applicable

Relevant identified uses of the substance or mixture and uses advised against

Flashing Cement

Details of the supplier of the safety data sheet

Company Name

Everkem Diversified Products
120 Regent Drive
Winston-Salem, NC 27106 USA

Emergency

24 hour Emergency Telephone No.

Everkem Diversified Products
Tel: 1-800-638-3160
Hours of Operation: M-F 9:00 am - 5:00 pm EST

Customer Service:

Tel: 1-800-638-3160
Fax: (336) 661-7969
Web Site: www.everkemproducts.com

Section 2. Hazard(s) identification

Classification of the substance or mixture under US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Flammable Liquid, category 3;H226

Flammable liquid and vapor.

Skin corrosion/irritation category 2;H315

Causes skin irritation.

Serious eye damage / eye irritation, category 1;H318

Causes serious eye damage.

Specific target organ toxicity, repeated exposure category 1;H372

Causes damage to organs through prolonged or repeated exposure. Specific Target Organs: (central nervous system)

Aquatic toxicity (chronic), category 2;H411

Toxic to aquatic life with long lasting effects.

Label elements



Danger



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

H226 Flammable liquid and vapor.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H372 Causes damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

[Prevention]

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

P233 Keep container tightly closed.

P240 Ground and bond container and receiving equipment.

P241 Use explosion-proof electrical, ventilating, light, equipment.

P242 Use non-sparking tools.

P243 Take action to prevent static discharges.

P260 Do not breathe dust, fume, mist, vapors or spray.

P262 Do not get in eyes, on skin, or on clothing.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

[Response]

P301+310 IF SWALLOWED: Immediately call a POISON CENTER, doctor or physician.

P302+352 IF ON SKIN: Wash with plenty of soap and water.

P303+361+353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER, doctor or physician.

P314 Get Medical advice or attention if you feel unwell.

P331 Do NOT induce vomiting.

P332+313 If skin irritation occurs: Get medical attention.

P362+364 Take off contaminated clothing and wash it before reuse.

P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.

P391 Collect spillage.

[Storage]

P403+235 Store in a well ventilated place. Keep cool.

[Disposal]

P501 Dispose of contents or container in accordance with local and national regulations.

Other hazards

This product contains no PBT/vPvB/vPvM chemicals.

This product contains no endocrine disrupting chemicals.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Does NOT contain component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS) per the US EPA PFASMASTER combined list of PFAS chemicals.

Section 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17) (GHS revision 7)

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Asphalt (petroleum) CAS Number: 8052-42-4 Synonyms: Asphalt	45 - 70	Not Classified	-----
Stoddard solvent CAS Number: 8052-41-3 Synonyms: White spirits	10 - 30	Specific target organ toxicity, repeated exposure category 1;H372 Aspiration hazard, category 1;H304	-----
Fullers earth CAS Number: 8031-18-3 Synonyms: Hydrous Alumino Silicate, hydrated magnesium aluminum silicate (Fuller's Earth)Attapulgitte Clay	10 - 30	Not Classified	-----
Cellulose CAS Number: 9004-34-6 Synonyms: No available information	3 - 7	Combustible Dust	-----
1-Propanamine, 3-(isodecyloxy)-, acetate CAS Number: 28701-67-9 Synonyms: No available information	3 - 7	Acute toxicity(oral), category 4;H302 Skin corrosion/irritation category 1B;H314 Aquatic toxicity (chronic), category 1;H410	-----
SBS Mixture CAS Number: Proprietary Synonyms: No available information	3 - 7	Not Classified	-----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT, vPvM or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General

In all cases of doubt, or when symptoms persist, seek medical attention.
Never give anything by mouth to an unconscious person.

Skin: Moderately irritating.

Ingestion: Abdominal irritation.

Inhalation: If enlivened by primer or heat, over exposure to fume could cause irritation, dizziness.

Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Skin Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

Ingestion If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Overview Pre-existing eye, skin, and respiratory disorders may be aggravated by exposure to these products. Exposure to high concentrations of fumes may have an anesthetic effect. No chronic toxicity or long term toxicity information available. Treat symptomatically. Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Eyes Causes serious eye damage.

Skin Causes skin irritation.

Section 5. Fire-fighting measures

Extinguishing media

:Suitable Extinguishing Media:

Use dry chemical, CO₂, water spray(FOG) or foam.

:Unsuitable Extinguishing Media:

Avoid solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture

Hazardous decomposition: Combustion: carbon dioxide (CO₂), carbon monoxide (CO), nitrogen oxides, smoke, and fumes.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.

Keep container tightly closed.

Ground and bond container and receiving equipment.

Use explosion-proof electrical, ventilating, light, equipment.

Use non-sparking tools.

Take action to prevent static discharges.

Do not breathe dust, fume, mist, vapors or spray.

Do not get in eyes, on skin, or on clothing.

Advice for fire-fighters

When heated above flash point, material will release flammable vapors which can burn or be explosive in confined spaces if ignited. Do not mix with strong oxidants such as liquid chlorine or concentrated oxygen. Elevated temperatures can lead to the formation of irritating vapors.

Minimize breathing vapors, gases or fumes of decomposition products. Do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

If the fire does not respond to above agents or they are not available, use foam or water FOG as a last resort. Water may also be used to cool exposed, but not burning, containers. These products may float and be re-ignited on top of water.

Closed containers may explode in a fire. Keep containers cool and remove to a safe location.

In a confined space, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face-piece and protective clothing. Persons without respiratory protection should leave area.

ERG Guide No. 128

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Environmental precautions

Do not allow spills to enter drains or waterways.

Methods and material for containment and cleaning up

Eliminate Sources of ignition and ventilate the area. Add sand or earth or absorb spill with suitable absorbent material and place in a closed container. Keep products out of sewers and waterways by diking or impounding. Advise authorities if product has entered or may enter sewers or waterways. Assure conformity with applicable governmental regulations.

Section 7. Handling and storage

Precautions for safe handling

Store in cool, dry area, away from heat, sparks and naked flames.

Keep containers sealed when not in use.

Vapors are heavier than air and may travel along the ground or be moved by ventilation to locations distant from the point of material handling. Avoid prolonged or repeated inhalation of vapors or spray mists. Avoid prolonged or repeated skin contact. Adhere to good hygienic practices. Avoid open flames. Use with adequate ventilation.

Health studies have shown that many petroleum hydrocarbons pose potential human health risks which may vary from person to person. As a precaution, exposure to liquids, vapors, mists or fumes should be minimized.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place, out of direct sunlight and away from heat, sparks, and flame. To prevent fumes from entering buildings or confined areas, close all air intake sources near the material handling or the work area. To prevent ignition, avoid smoking, keep away from heat, open flames and sources of static or electrical sparking. Use explosion proof motors and equipment. Tank trucks or other containers should be grounded and/or bonded when the material is transferred.

Incompatible materials: May react with strong oxidizing materials

See section 2 for further details. - [Storage]

Specific end use(s)

No data available.

Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Section 8. Exposure controls / personal protection

Control parameters

Exposure Limits

CAS No.	Ingredient	Source	Value
8031-18-3	Fullers earth	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
8052-41-3	Stoddard solvent	ACGIH	TWA: 100 ppm
		OSHA	500 ppm, 2900 mg/m ³
		NIOSH	TWA 350 mg/m ³ C 1800 mg/m ³ [15-minute]
		Alberta	100 ppm TWA; 572 mg/m ³ TWA
		British Columbia	290 mg/m ³ TWA 580 mg/m ³ STEL
		Manitoba	100 ppm TWA
		New Brunswick	100 ppm TWA; 525 mg/m ³ TWA
		Newfoundland and Labrador	100 ppm TWA
		Nova Scotia	100 ppm TWA
		Northwest Territories	100 ppm TWA 125 ppm STEL
		Nunavut	100 ppm TWA 125 ppm STEL
		Ontario	525 mg/m ³ TWA (140C Flash aliphatic solvent)
		Prince Edward Island	100 ppm TWA
		Quebec	100 ppm TWAEV; 525 mg/m ³ TWAEV
		Saskatchewan	100 ppm TWA 125 ppm STEL



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

8052-42-4	Asphalt (petroleum)	Yukon	100 ppm TWA; 575 mg/m ³ TWA 150 ppm STEL; 720 mg/m ³ STEL
		ACGIH	TWA: 0.5 mg/m ³ (I) Inhalable
		OSHA	No Established Limit
		NIOSH	Ca C 5 mg/m ³ [15-minute]
		Alberta	5 mg/m ³ TWA (Petroleum; Bitumen, fume)
		British Columbia	0.5 mg/m ³ TWA (inhalable fume, as Benzene-soluble aerosol)
		Manitoba	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as Benzene-soluble aerosol)
		New Brunswick	5 mg/m ³ TWA (petroleum fumes)
		Newfoundland and Labrador	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as Benzene-soluble aerosol)
		Nova Scotia	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as Benzene-soluble aerosol)
		Northwest Territories	0.5 mg/m ³ TWA (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction)) 1.5 mg/m ³ STEL (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction))
		Nunavut	0.5 mg/m ³ TWA (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction)) 1.5 mg/m ³ STEL (Bitumen, fume, as Benzene soluble aerosol (inhalable fraction))
		Ontario	0.5 mg/m ³ TWA (fume, inhalable, as Benzene-soluble aerosol)
		Prince Edward Island	0.5 mg/m ³ TWA (fume, inhalable particulate matter, as Benzene-soluble aerosol)
		Quebec	5 mg/m ³ TWA _{EV} (fume)
		Saskatchewan	0.5 mg/m ³ TWA (fume and inhalable fraction, as Benzene soluble aerosol) 1.5 mg/m ³ STEL (fume and inhalable fraction, as Benzene soluble aerosol)
		Yukon	5 mg/m ³ TWA (fume) 10 mg/m ³ STEL (fume)
9004-34-6	Cellulose	ACGIH	TWA: 10 mg/m ³
		OSHA	15 mg/m ³ (total dust), 5 mg/m ³ (respirable fraction)
		NIOSH	TWA 10 mg/m ³ (total) TWA 5 mg/m ³ (resp)
		Alberta	10 mg/m ³ TWA
		British Columbia	10 mg/m ³ TWA (total dust); 3 mg/m ³ TWA (respirable fraction)
		Manitoba	10 mg/m ³ TWA
		New Brunswick	10 mg/m ³ TWA
		Newfoundland and Labrador	10 mg/m ³ TWA
		Nova Scotia	10 mg/m ³ TWA
		Northwest Territories	10 mg/m ³ TWA 20 mg/m ³ STEL
		Nunavut	10 mg/m ³ TWA 20 mg/m ³ STEL
		Ontario	10 mg/m ³ TWA
		Prince Edward Island	10 mg/m ³ TWA
		Quebec	10 mg/m ³ TWA _{EV} (containing no Asbestos and <1% Crystalline silica, total dust)
		Saskatchewan	10 mg/m ³ TWA 20 mg/m ³ STEL
		Yukon	30 mppcf TWA; 10 mg/m ³ TWA 20 mg/m ³ STEL



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

28701-67-9	1-Propanamine, 3-(isodecyloxy)-, acetate	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
Proprietary	SBS Mixture	ACGIH	No Established Limit
		OSHA	No Established Limit
		NIOSH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit

Exposure controls

Respiratory

In case of burning material, use SCAB.

Eyes

Wear safety glasses with side shields to protect the eyes. An eye wash station is suggested as a good workplace practice.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Skin	Protective clothing as necessary to prevent wetting of the skin. Wear PVC or rubber gloves to keep skin contact to a minimum. Refer to the manufacturer's recommendations regarding the suitability of any gloves used.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Information on basic physical and chemical properties

Physical State	Liquid
Color	Dark
Odor	Mild Petroleum
Odor threshold	Not Available
Melting point / freezing point	Not Available
Initial boiling point and boiling range	300-350 °F
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Available Upper Explosive Limit: Not Available
Flash Point	104°F min.(PMCC)
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
pH	Not Available
Viscosity (cSt)	Not Available
Solubility in Water	Insoluble in Water.
Partition coefficient n-octanol/water (Log Kow)	Not Available
Vapor pressure (Pa)	3
Relative Density	1.0 - 1.05
Vapor Density	(Air = 1): >4
Evaporation rate (Ether = 1)	(Butyl Acetate=1)@ 77°F: 0.2
VOC Content	Not Available

Other information

No other relevant information.



Safety Data Sheet Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Section 10. Stability and reactivity

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No data available.

Conditions to avoid

Keep away from heat, spark, open flames. Auto-ignition temperature unknown.

Incompatible materials

May react with strong oxidizing materials

Hazardous decomposition products

Combustion: carbon dioxide (CO₂), carbon monoxide (CO), nitrogen oxides, smoke, and fumes.

Section 11. Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation, and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Asphalt (petroleum) - (8052-42-4)	No data available.	No data available.	No data available.	No data available.	No data available.
Stoddard solvent - (8052-41-3)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	5.50, Rat - Category: NA	No data available.
Fullers earth - (8031-18-3)	No data available.	No data available.	No data available.	No data available.	No data available.
Cellulose - (9004-34-6)	> 5,000.00, Rat - Category: NA	No data available.	No data available.	No data available.	No data available.
1-Propanamine, 3-(isodecyloxy)-, acetate - (28701-67-9)	No data available.	No data available.	No data available.	No data available.	No data available.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

SBS Mixture - (Proprietary)	No data available.	No data available.	No data available.	No data available.	No data available.
-----------------------------	--------------------	--------------------	--------------------	--------------------	--------------------

Carcinogen Data

CAS No.	Ingredient	Source	Value
8031-18-3	Fullers earth	IARC	No
		ACGIH	No Established Limit
8052-41-3	Stoddard solvent	IARC	No
		ACGIH	No Established Limit
8052-42-4	Asphalt (petroleum)	IARC	Group 2b
		ACGIH	A4
9004-34-6	Cellulose	IARC	No
		ACGIH	No Established Limit
28701-67-9	1-Propanamine, 3-(isodecyloxy)-, acetate	IARC	No
		ACGIH	No Established Limit
Proprietary	SBS Mixture	IARC	No
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	1	Causes serious eye damage.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	1	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	---	Not Applicable

Possible routes of entry:

Inhalation, ingestion, skin contact, and skin absorption.

Symptoms and effects, both acute and delayed:

Pre-existing eye, skin, and respiratory disorders may be aggravated by exposure to these products. Exposure to high concentrations of fumes may have an anesthetic effect. No chronic toxicity or long term toxicity information available. Treat symptomatically.

Eyes Causes serious eye damage.

Skin Causes skin irritation.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Section 12. Ecological information

Toxicity

Toxic to aquatic life with long lasting effects.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Asphalt (petroleum) - (8052-42-4)	No data available.	No data available.	No data available.
Stoddard solvent - (8052-41-3)	No data available.	No data available.	No data available.
Fullers earth - (8031-18-3)	No data available.	No data available.	No data available.
Cellulose - (9004-34-6)	100.00, Fish (Piscis)	No data available.	No data available.
1-Propanamine, 3-(isodecyloxy)-, acetate - (28701-67-9)	No data available.	No data available.	No data available.
SBS Mixture - (Proprietary)	No data available.	No data available.	No data available.

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

Not Available

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB/vPvM chemicals.

Other adverse effects

No data available.

Section 13. Disposal considerations

Waste treatment methods

Bury in an approved landfill according to federal, state, and local regulations. Empty containers that have been completely emptied and the residue allowed to dry are not considered hazardous waste.

Section 14. Transport information



	DOT (Domestic Surface Transportation)	TDG (Domestic Surface Transportation)
UN number	UN1993	UN1993
UN proper shipping name	Flammable liquids, n.o.s., (Asphalt Cements and Coatings Non-Bulk)	Flammable liquids, n.o.s., (Asphalt Cements and Coatings Non-Bulk)
Transport hazard class(es)	Class: 3	Class: 3 Sub Class: Not Applicable
Packing group	III	III

	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	UN1993	UN1993
UN proper shipping name	Flammable liquids, n.o.s., (Asphalt Cements and Coatings Non-Bulk)	Flammable liquids, n.o.s., (Asphalt Cements and Coatings Non-Bulk)
Transport hazard class(es)	Class: 3 Sub Class: Not Applicable	Class: 3 Sub Class: Not Applicable
Packing group	III	III

Environmental hazards

IMDG Marine Pollutant: Yes; (1-Propanamine, 3-(isodecyloxy)-, acetate)

Special precautions for user

Not Applicable



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Section 15. Regulatory information

Regulatory Overview The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

This product has been classified in accordance with US OSHA's Hazard Communication Standard (1910.1200) revised 2024 and Canadian Hazardous Products Regulations (SOR/2015-17 amended 2022-12-15) (GHS revision 7) and the SDS contains all of the information required by those regulations.

Toxic Substance Control Act (TSCA)

1-Propanamine, 3-(isodecyloxy)-, acetate

Asphalt (petroleum) (UVCB)

Cellulose (XU)

Fullers earth (UVCB)

Stoddard solvent (UVCB)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Canadian Domestic Substance List (DSL):

1-Propanamine, 3-(isodecyloxy)-, acetate

Asphalt (petroleum)

Cellulose

Fullers earth

Stoddard solvent

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Carcinogens (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 Label Warning:

This product contains no chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.



Safety Data Sheet

Roof Goo, All Weather Flashing Cement

Revision Date:
22 January, 2026

Section 16. Other information

Revision Date 22 January, 2026

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H372 Causes damage to organs through prolonged or repeated exposure.

H410 Very toxic to aquatic life with long lasting effects.

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document