

ROOF GOO

ALL-SEASON ROOF AND FLASHING CEMENT

PRODUCT NAME

Roof Goo - All-Season Roof and Flashing Cement

MANUFACTURER

Everkem Diversified Products
120 Regent Drive, Winston Salem, NC 27103
PH: 1-800-638-3160 | FAX: (336) 661-7969

PRODUCT DESCRIPTION

Roof Goo - All-Season Roof and Flashing Cement features a durable, permanently flexible formula that allows for easy application when patching holes and cracks. Ideal for emergency leak sealing, it performs on both wet and dry roof surfaces and provides strong adhesion, even underwater. Specially formulated for damp and wet roofing conditions, Roof Goo can also be used as a heavy-duty flashing cement for repairing flashings, asphalt shingles, built-up roofs, metal, and masonry surfaces. It is well suited for sealing leaks and openings around common flashing areas such as chimneys, vents, skylights, metal joints, and gutters.

APPLICATIONS

- Asphalt shingles
- Built-up roofs
- Metal
- Masonry

ADVANTAGES

- Meets ASTM-4586 Type I and ASTM D-3409
- Flexible formula for long-term durability
- Seals leaks on wet or dry surfaces
- Ideal for emergency roof repairs
- Works on multiple roofing materials

LIMITATIONS

Do not use with EPDM, PVC, TPO, or other single-ply roofing membranes. DO NOT THIN. DO NOT HEAT CONTAINER. DO NOT store in an area where temperatures exceed 120°F.

AVAILABLE COLORS

Roof Goo is available in Black.

TECHNICAL DATA

TYPICAL PHYSICAL PROPERTIES

Typical Uncured Properties

Chemistry:	Asphalt cement
Uncured State:	Dark liquid
Odor:	Mild petroleum odor
Application Temperature:	20°F (-6°C) and 120°F (48°C)
Tooling Time:	15 - 30 minutes
Full Cure Time:	48 hours
Shelf Life:	12 months
Flash Point:	104°F (40°C) minimum

Typical Cured Properties

Cured State:	Firm paste
ASTM 4586 Type I:	Meets ASTM 4586 Type I "Standard Specification for Asphalt Roof Cement"
ASTM D-3409:	Meets ASTM D-3409 "Standard Test Method for Adhesion of Asphalt-Roof Cement to Damp, Wet, or Underwater Surfaces"
Service Temperature:	Up to 180°F (93°C)
V.O.C. Content:	Less than 300 g/L

ROOF GOO

ALL-SEASON ROOF AND FLASHING CEMENT

TECHNICAL DATA [CONT]

APPLICABLE STANDARDS & SPECIFICATIONS

SPECIFIED DIVISIONS

- Section 07 92 00 - Joint Sealants
- Section 07 60 00 - Flashing and Sheet Metal
- Section 07 50 00 - Membrane Roofing

APPLICABLE STANDARDS/SPECIFICATIONS

- ASTM 4586 Type I - Standard Specification for Asphalt Roof Cement
- ASTM D-3409 - Standard Test Method for Adhesion of Asphalt-Roof Cement to Damp, Wet, or Underwater Surfaces

INSTALLATION

SURFACE PREPARATION

Surfaces should be clean of any debris or material that may prevent or deter adhesion. Such debris includes, but is not limited to: dirt, frost, loose particles, existing sealants, grease, oils, rust, etc. In colder climates, it is recommended storing the product at room temperature for 24 hours prior to application.

APPLICATION

1. Cut and pre-fit materials before applying the product and installing.
2. Cut nozzle to desired bead size. Apply approximately 1/8" thickness of cement onto problem area.
3. For best results, complete tooling within 10 minutes.

CLEANUP

Excess cement should be cleaned off tools and surfaces while it is in the uncured state using water and a dry cloth or paper towels.

AVAILABILITY

Roof Goo and other Everkem products are available from stocking distributors nationwide or direct from the manufacturer. For the name and telephone number of the nearest Everkem representative, call the number below or visit www.everkemproducts.com

PACKAGING OPTIONS

PACKAGING OPTIONS

Part #	Description	Packaging	Color
RC365-10	Roof Goo - 10.1 Fl. Oz. (298.69 mL) Tube	12 tubes/case	Black

MAINTENANCE

Inspect cement and strength of adhesion of application at a minimum of every five years. If cement or bond of cement is damaged, completely remove or cut away sealant in the damaged area, clean surface, and reapply cement.

ROOF GOO

ALL-SEASON ROOF AND FLASHING CEMENT

TECHNICAL SERVICES

Everkem representatives are available to assist you in selecting the sealant or adhesive appropriate for your application. For further assistance contact your local Everkem Diversified Products representative, call our corporate office at 1-800-638-3160, or contact us via our website at www.everkemproducts.com

WARRANTY

Everkem Diversified Products warrants this product's performance provided it is properly stored and applied within 18 months. If when applied as directed this material proves to be defective, return the remaining product and proof of purchase for refund or replacement of product exclusive of labor or cost of labor. This is the sole and exclusive remedy for defects of product failure. The determination of eligibility for this warranty shall be made at the sole discretion of Everkem Diversified Products and any decision made shall be final. This warranty is in lieu of any other warranties, expressed or implied, including but not limited to a warranty of merchantability or fitness for a particular purpose, and in no instance will Everkem Diversified Products be liable for damages in excess of the purchase price, except where such exclusion or limitation is prohibited by state law. Users must read and follow the directions of the current Technical Data Guide and SDS prior to product use. The user determines the suitability of the product intended for use and assumes all risks. Recommendations for the use of this product are based on tests we believe to be reliable. The manufacturer and seller are not responsible for results where the product is used under conditions not in strict accordance with our published recommendations and in applications considered suitable for this product. Everkem Diversified Products shall not be responsible for the use of this product in a manner to infringe upon any patent or any other intellectual property rights held by others.

CAUTIONS



DANGER: FLAMMABLE LIQUID AND VAPOUR. CAUSES SKIN AND EYE IRRITATION. Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling. **IF ON SKIN:** Wash with soap and water. Remove contaminated clothing, washing before reuse. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water.

Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. **IF INGESTED:** Wash mouth with water. Remove victim to fresh air. Give small quantities of water to drink. Do not induce vomiting. Store locked up. Dispose of contents in accordance with all local, regional, national, and international regulations. Avoid prolonged or repeated inhalation of vapors or spray mists. Avoid open flames. Use with adequate ventilation. Store in a cool, dry place, out of direct sunlight and away from heat, sparks, and flame. **KEEP OUT OF REACH FROM CHILDREN.**



WARNING: This product may contain trace amounts of crystalline silica, which is considered a hazard by inhalation that can cause silicosis. Petroleum asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Everkem Diversified Products
120 Regent Drive | Winston-Salem, NC | 27103
1-800-638-3160 | www.everkemproducts.com

Last Revised: 3/2026